


RV Adhesive Sealant

Product Features and Benefits

- Neutral cure silicone
- Excellent tooling characteristics
- Service Temperature -40 F to +400 F
- Application Temperature -20 F to +120 F
- UV and Mildew Resistant
- VOC compliant in all 50 states
- Waterproof
- Will not sag or slump, shrink or crack
- Permanently flexible
- Weather tight seal
- Low odor
- Solvent free
- Invisible to UV light
- Easily gunned at all temperatures
- 18 month shelf life
- Tack free in 10 minutes; cured in 48 hrs

Available Colors:



White
RV100



Black
RV110




Gray
RV111



Imperial Brown
RV130



Sandstone
RV146



Translucent
RV150



Product Information

- Description - RV Adhesive Sealant
- Item Number - 02-RV0XXXX-10C1
- Size - 10.3 FL. OZ (304 mL)
- Unit Dimensions - 9" X 2" X 2"

Case Pack Information

- Description - RV Adhesive Sealant
- Item Number - 02-RV0XXXX-10C1
- Dimensions - 11 15/16" X 9 15/16" X 8 1/8"
- Case Weight - 10 lbs - 12 packs
- Cases Per Pallet - 120 - 12 packs

RV Adhesive Sealant

Technical Information

Product: Novaflex
 RV Adhesive Sealant
 Appearance: Smooth paste
 Application Temperature:
 -20 °F to +120°F
 (-28°C to 50°C)
 Service Temperature:
 -40°F to +400°F
 (-40°C to 200°C)
 Adhesion: Excellent to most common building materials
 Consistency: Non-sag
 Bridging Ability: Excellent, bridges gaps to 3/4" (2 cm)
 Gunning Extrusion:
 Very easy to gun and clean up
 Durability: +/- 25% joint movement
 Flexibility: Remains flexible to -40°F
 Water Resistance: Excellent
 - Not to be submerged
 Exterior Weathering:
 Excellent
 Aging: Excellent
 Freeze-Thaw Stable:
 Will Not Freeze
 Odor: None
 Skin Time:
 • 40°F/40% relative humidity – 40 minutes
 • 75°F/50% relative humidity – 10 minutes
 • 95°F/95% relative humidity – 5 minutes
 Through and Cure Time:
 • 40°F/60% relative humidity – 2-3 days
 • 75°F/50% relative humidity – < 24 hrs
 Weight per gallon: 10.2 pounds
 Solids: 97%
 Flash Point: > 400°F

Novaflex RV Adhesive Sealant is utilized in the transportation industry including truck-trailer, truck body, cargo container, travel trailer, manufactured housing, and recreational vehicle (RV) industries. Excellent expansion and contraction properties and will withstand joint movement and temperature changes associated with transporting manufactured units.

Product Specs

Coverage: 28 linear ft. using a 1/4" bead

Specifications: Meets or exceeds the performance characteristics of: ASTM C-920, AAMA 802.3, 805.2, 808.3, TT-S-001543A and TT-S-230C.

Shelf life: Use product within 18 months from manufacturers date. FREEZE THAW STABLE. Store product at 40°F to 80°F.

MAX VOC: less than 34 g/l (<4% by weight). VOC compliant in all 50 states.

Recommended For Sealing

- Tent Campers
- Toy Haulers
- Travel Trailers
- Motorhomes
- Fifth Wheels
- Recreational Vehicles (RV)

Not Recommended For

- Joints continuously submerged under water
- Areas needing paint or stain
- Spaces confined from atmospheric moisture during cure
- On surfaces that might bleed oils, plasticizers or solvents
- In structural glazing applications
- Painted Applications

Limited Warranty: Satisfaction guaranteed when handled and applied according to label instructions. Call 1-800-380-0138 for Customer Service.

CAUTION!: Methyl ethyl ketoxime, methyl and ethyl alcohol released during cure. Avoid breathing vapors. Avoid prolonged or repeated skin contact.

KEEP OUT OF REACH OF CHILDREN

First Aid: Skin: Wash with soap and water. Eyes: SEEK IMMEDIATE MEDICAL ATTENTION. Inhalation causing discomfort: Remove to fresh air. If discomfort persists or any breathing difficulty occurs, or if swallowed, SEEK IMMEDIATE MEDICAL ATTENTION. Additional information please refer to MSDS.

Disposal: For disposal of material follow federal, state and local regulations.



NOVAGARD
 Solutions™
 Engineered Products... Innovative Thinking

5109 Hamilton Ave.
 Cleveland, OH 44114
 1-800-380-0138
 www.novagard.com
 Made in USA. For commercial use.