


Seam Sealer

Product Features and Benefits

- Professional Grade
- Low Odor
- Self Leveling
- Neutral Cure
- Quick Drying
- Permanently Flexible


Available Stock Colors



White
MX2100



Lincoln Bronze
MX2121



Beige
MX2140



Sandstone
MX2146



Translucent
MX2257

Product Specs

Coverage: 28 linear ft. using a 1/4" bead

Specifications: Meets or exceeds the performance characteristics of:
AAMA 803.3, Type II

Product Information

Description - Novaflex Seam Sealer

Item Number - 02-MX2XXX-10C1

Size - 5 FL. OZ (146 mL)



AAMA Verified

Seam Sealer

Novaflex Seam Sealer is designed for rivet, corner and butt joint seams, as well as screw heads.

Recommended For Sealing

- Rivets
- Gutters
- Corner Joints
- Screw heads
- Butt Joints

Not Recommended For

- Joints continuously submerged under water
- Areas needing paint or stain
- Spaces confined from atmospheric moisture during cure
- On surfaces that might bleed oils, plasticizers or solvents
- In structural glazing applications
- Painted Applications

WARNING

H227: Combustible liquid

H303: May be harmful if swallowed

H316: Causes mild skin irritation

H333: May be harmful if inhaled

H320: Causes eye irritation

P210: Keep away from heat/spark/open flames. No smoking

P264: Wash thoroughly after handling

P312: Call a doctor if you feel unwell

P332: If skin irritation occurs get medical attention

P337: If eye irritation persists get medical attention

Shelf life: Use product within 18 months from manufacturers date. FREEZE THAW STABLE. Store product at 40°F to 80°F.

MAX VOC: less than 34 g/l (<4% by weight). VOC compliant in all 50 states.

Disposal: For disposal of material follow federal, state and local regulations.



NOVAGARD
Solutions
Engineered Products... Innovative Thinking

5109 Hamilton Ave.
Cleveland, OH 44114
1-800-380-0138
www.novagard.com
Made in USA. For commercial use.